



**JINSP Company Ltd.**  
spectralanalyser.com

## JINSP SR100Q High Sensitivity Fiber Optic Spectrometer for Accurate Film Thickness Measurement Spectral Range 200nm 1100nm

### Our Product Introduction

for more products please visit us on [spectralanalyser.com](http://spectralanalyser.com)

#### Basic Information

- Place of Origin: CHINA
- Brand Name: JINSP
- Certification: ISO9001
- Model Number: SR100Q
- Minimum Order Quantity: 1
- Price: Negotiable
- Packaging Details: International Shipping Package
- Delivery Time: 90-120 working days
- Payment Terms: T/T, Western Union
- Supply Ability: 100PCS/90-120 days



#### Product Specification

- Spectral Range: 200nm - 1100nm
- Effective Pixels: 1024\*122
- Quantum Efficiency: QE92%peak@650nm, 83%@232nm
- SNR: 1000:1
- Highlight: High Sensitivity Fiber Optic Spectrometer, 200nm-1100nm Fiber Optic Spectrometer



#### More Images



## Product Description

### 92% High Quantum Spectrometer for Film Thickness Measurement

Modern industries leveraging thin film technology require sophisticated measurement approaches. Photoelectric methods deliver unparalleled advantages: zero sample alteration coupled with instant readings. The synergy of optical sensors and computational analytics paves the way for smarter production techniques and enhanced material performance.

The JINSP SR100Q spectrometer is integrated with the Hamamatsu S7031, a scientific-grade TE-cooled area array CCD chip. With a pixel size of up to 24\*24μm and excellent quantum efficiency of up to 92%, it ensures high response in the ultraviolet band and effectively improves the sensitivity and SNR of weak signals. Furthermore, it can realize excellent spectrum signals, and stable and reliable performance based on the advanced high-resolution light path and low-noise, high-speed FPGA signal processing chip.

#### Product Parameters:

Detector	Chip Type	Back-illuminated TE-cooled Hamamatsu S7031
	Effective Pixel	1024*122
	Pixel Size	24*24μm
	Sensing Area	24.576*2.928mm
Optical Parameters	Optical Design	F/4 cross-type
	Numerical Aperture	0.13
	Focal Length	100mm
	Entrance Slit Width	10μm,25μm,50μm,100μm,200μm (customizable)
Electrical Parameters	Fiber Interface	SMA905,free space
	Integration Time	8ms-3600s
	Data Output Interface	USB3.0,RS232,RS485,20pin connector
	ADC Bit Depth	16-bit
	Power Supply	5V
Physical Parameters	Operating Current	<3.5A
	Operating Temperature	10 ~40
	Storage Temperature	-20 ~60
	Operating Humidity	<90%RH (no condensation)
	Dimensions	180mm*120mm*50mm
	Weight	1.2kg

#### List of Product Models:

Model	Spectral Range(nm)	Resolution(nm)	Slit(μm)
SR100Q-G21	200~950	6.8	200
		2.2	50
SR100Q-G22	350~1100	1.5	25
		1.0	10
SR100Q-G23	200~775	1.6	50
		1.0	25
SR100Q-G24	350~925	0.7	10
SR100Q-G25	532~690(4400cm <sup>-1</sup> )*	13cm <sup>-1</sup>	50
SR100Q-G26	638~800(3200cm <sup>-1</sup> )*	10cm <sup>-1</sup>	25
SR100Q-G27	785~1050(3200cm <sup>-1</sup> )*	11cm <sup>-1</sup>	50

**Note: The\*are primarily designed for Raman applications, with the corresponding Raman.**

#### Technical Characteristics:

High quantum efficiency, 92%peak@650nm, 83%@232nm

High SNR: Ultra-low dark noise under long integration time, SNR is as high as 1000:1

Noise-free clear processing of weak signal in long exposure, strong adaption to environment


Low-noise and high-speed circuit: USB3.0

#### Measurement Method:

A fiber-coupled light source illuminates the film, inducing reflections at both interfaces. The spectrometer detects the interference of these beams, allowing thickness (d) determination via the extremum method (θ, n, and spectral extrema).

Fringe density scales with thickness but diminishes at longer wavelengths. Proper wavelength range and resolution ensure

measurement validity.



**Typical Applications:**

Detect absorption, transmittance and reflection Spectrum

Light source and laser wavelength characterization

OEM product module: Fluorescence spectrum, Raman spectrum, etc.


## Ultra High Sensitivity Fiber Optic Spectrometer

Research-grade CCD chip S7031

# SR100Q



# Technical Characteristics



High quantum efficiency,  
92%peak@650nm,  
83%@232nm



High SNR: Ultra-low dark noise  
under long integration time,  
SNR is as high as 1000:1



Noise-free clear  
processing of weak signal  
in long exposure, strong  
adaption to environment



Low-noise and high-speed  
circuit: USB3.0

## Typical Applications


Detect absorption, transmittance and  
reflection Spectrum




Light source and laser wavelength  
characterization




OEM product module: Fluorescence  
spectrum, Raman spectrum, etc.





CCD Quantum Efficiency Curve



Installation dimension drawing

### Company Introduction:

JINSP Company Limited, abbreviated as "JINSP", is a professional supplier with over 17 years of experience in spectral detection technology products, including Raman, FT-IR, LIBS technologies, etc. After 17 years of technology accumulation, the company's core key technologies have reached the international leading position at the level, and the cumulative number of patent applications exceeded 200.

In addition to its main headquarters located in the bustling city of Beijing, JINSP has established a fully owned subsidiary manufacturing facility situated in the province of Jiangsu, China.

JINSP Company received ISO9001:2015, ISO14001:2015, and ISO45001:2018 certifications. JINSP can provide required certifications, such as certification by the Ministry of Public Security or National Institute of Metrology, Environmental Level Certification, IP Level Certification, CE Certification, Transport Identification Report, EU ECAC certification, German ICT Security Testing, etc.



# Company Profile



# Exhibition



# Certifications



## FAQ

Q1: This is the first time I use, is it easy to operate?

A1: We will send you manual and guide video in English, it can teach you how to operate the spectrometer. Also our technicians will offer professional technical operation meetings.

Q2: Can you offer a operation training?

A2: Your technicians can come to our factory for a training. Jinsp engineers can go to your place for local support ( installation, training, debugging, maintenance ).

Q3: What's your website?

A3: You can visit: [www.jinsptech.com](http://www.jinsptech.com)

Q4: What about your quality assurance?

A4: We have a quality inspection team. All goods will go through quality inspection before shipment. We can send you pictures for inspection.



JINSP

JINSP Company Ltd.



8618620854039



[phoebeyu@jinsptech.com](mailto:phoebeyu@jinsptech.com)



[spectralanalyser.com](http://spectralanalyser.com)

21st Floor, Building D, Tsinghua Tongfang Science and Technology Plaza, Haidian District, Beijing China